



1101 Victoria Curve | Mendota Heights, MN 55118  
651.452.1850 phone | 651.452.8940 fax  
www.mendota-heights.com

## SEWER PERMIT APPLICATION

PROPERTY ADDRESS \_\_\_\_\_ DATE OF APPLICATION \_\_\_\_\_

PROPERTY OWNER (Name) (Address) (Phone)

CONTRACTOR (Name) (Address) (Phone)

CONTACT PERSON (Name) (Phone)

**Please call Rich Burrows at 651-587-9179 48 hours in advance to schedule an inspection**

Property Type:	<input type="checkbox"/> Commercial <input type="checkbox"/> Residential			
Description of Work:	<input type="checkbox"/> New Property Hook- Up <b><u>OFFICE STAFF TO COMPLETE</u></b> SAC PAYMENT INFORMATION DATE PAID:  PERMIT #:	<input type="checkbox"/> Repair	<input type="checkbox"/> Disconnect	<input type="checkbox"/> Other (please explain below)  <hr/> <hr/> <hr/>

City Office Use Only:	
Permit Fee	\$ 75.00
State Surcharge	\$ 1.00
Total Fee	\$ 76.00

### ACKNOWLEDGMENT AND SIGNATURE

The undersigned hereby represents upon all of the penalties of law, for the purpose of including the City of Mendota Heights to take the action herein requested, that all statements herein are true and that all work herein mentioned will be done in accordance with the Ordinances of the City of Mendota Heights, the State of Minnesota, and Rulings of the Building department.

1. All contractors and subcontractors shall be licensed in accordance with City and State requirements.
2. This permit may be revoked at any time upon violation of any of the provisions of the City Building and Zoning Codes.
3. All inspections will be by City Staff. Do not backfill prior to inspection. Photo/video from contractor in place of visual inspection will NOT be accepted unless pre-approval by City Staff.
4. Disconnect shall be capped at ROW or as close as possible with pre-approval from City Staff if reinstatement is planned. If abandoning service, disconnect shall be at the wye connection to the main.
5. New building sewer pipe must meet standards set forth in Table 701.2 of the 2020 MN Plumbing Code. Maximum bend of fittings shall not exceed 22.5 degrees.
6. Any existing/left in place pipe (except structurally sound DIP or CIP as determined by the City) MUST be lined (including portion from disconnect to main) and jetted such that the lined sewer and connection is free of any remaining debris or lining material. Following lining and jetting operations, the line must be televised at the time of inspection. Structurally sound DIP or CIP must also be televised to demonstrate lack of infiltration. All lining operations are subject to procedures and requirements identified within the "Lining of Private Sewer Pipes in The City of Mendota Heights Specifications".

APPLICANT SIGNATURE

CITY APPROVAL

City Office Use Only:

Date Permit Issued:	Permit Number:
---------------------	----------------